

# Vacuum & Recovery



## VPX7

### 10 CFM Vacuum Pump

- 10 CFM flow rate with 15 microns ultimate vacuum
- ¾ HP DC motor
- Weighs 24 lbs. - Patented lightest weight
- RunQuick® Oil Change System offers on-the-fly oil changes in seconds
- Port Sizes: (1) 1/4", (2) 3/8", (1) 1/2"
- Small footprint – 1,346 cubic inches



## OIL8X3

### 3 Pack Vacuum Pump Oil

- Three eight-ounce containers of vacuum pump oil
- Low vapor pressure ideal for pulling vacuums
- Wide temperature range helps oil perform in any conditions
- Highly refined for consistent performance
- Ensures proper sealing and lubrication
- Designed to work with our RunQuick® Oil Change System



## VP87

### 8 CFM Vacuum Pump

- 8 CFM flow rate with 15 microns ultimate vacuum
- ¾ HP DC motor
- Weighs 27 lbs.
- RunQuick® Oil Change System offers on-the-fly oil changes in seconds
- Port Sizes: (1) 1/4", (2) 3/8", (1) 1/2"
- Small footprint – 1,346 cubic inches



## OIL32

### Quart Vacuum Pump Oil

- Quart-size container of vacuum pump oil
- Low vapor pressure ideal for pulling vacuums
- Wide temperature range helps oil perform in any conditions
- Highly refined for consistent performance
- Ensures proper sealing and lubrication
- Designed to work with our RunQuick® Oil Change System



## VP67

### 6 CFM Vacuum Pump

- 6 CFM flow rate with 15 microns ultimate vacuum
- ½ HP AC motor
- Weighs 29 lbs.
- RunQuick® Oil Change System offers on-the-fly oil changes in seconds
- Port Sizes: (1) 1/4", (2) 3/8", (1) 1/2"
- Small footprint – 1,346 cubic inches



## OIL128

### Gallon Vacuum Pump Oil

- Gallon-size container of vacuum pump oil
- Low vapor pressure ideal for pulling vacuums
- Wide temperature range helps oil perform in any conditions
- Highly refined for consistent performance
- Ensures proper sealing and lubrication
- Designed to work with our RunQuick® Oil Change System



## MG44

### Wireless Vacuum Gauge

- Confidently perform evacuations with a reliable, leak-proof seal
- Reversible angled coupler and new cylindrical design are easier to fit into tight spaces
- There are three ways to use: 1) Directly from the MG44's display, 2) up to 1000' away via the Job Link® mobile app, or 3) on the Fieldpiece SMAN® Refrigerant Manifold
- Three ways to view: New larger backlit LCD screen is easier to read and its dot-matrix display shows more info including 1) rate, 2) bar graph, and 3) rate meter
- IP54-rated weather-resistant



## MR45

### Digital Recovery Machine

- DC Motor: 1 HP (variable smart speed)
- Starts and runs easily with lower voltage
- Minimizes liquid slugging and maximizes vapor recovery
- Easy access ports
- Water resistant to withstand direct rain
- R32 Ready



## SR47

### Wireless Refrigerant Scale

- 13" platform to fit larger tanks
- Max load 252 lbs (114 kg)
- Water resistant
- 200 hour platform battery life
- Long range wireless
- Connect to Job Link® System Mobile App
- Integrated bumpers for increased durability



## SRS1

### Refrigerant Scale

- Charging & recovery weight alarms
- Easy to carry
- 0.25 oz (0.01 kg) resolution
- Maximum load: 110 lbs (50kg)
- Accuracy:  $\pm(0.05\%rdg + 10g)$
- Water resistant



## S365

### Charging Jacket for TXV Systems

- Charge from 37-70°F outside temperatures
- Service maintenance contracts before and after summer heat
- Extend billable hours
- Easy to adjust to reach correct pressure differential
- Looks professional

